



Low Frequency Double Wall Tubular Attenuator

Models **LRA** **LRB** **LRC**

Dynamic Insertion Loss (Db) Octave Band/Center Frequency (Hz)											
Model	Flow	Velocity fpm	Press Drop	1 63	2 125	3 250	4 500	5 1K	6 2K	7 4K	8 8K
LRA	Reverse	-3000	0.45	14	18	28	36	41	32	22	20
	Flow	-1500	0.11	13	18	27	35	42	35	23	21
		0		11	16	26	34	41	35	23	21
	Forward	+1500	0.11	10	15	25	32	40	35	24	21
	Flow	+3000	0.45	9	14	23	30	38	36	24	20
LRB	Reverse	-3000	0.19	12	14	25	30	36	26	19	16
	Flow	-1500	0.05	11	14	24	30	37	28	20	16
		0		10	12	23	29	37	29	20	17
	Forward	+1500	0.05	9	12	22	28	36	29	21	16
	Flow	+3000	0.19	8	11	20	26	34	30	21	15
LRC	Reverse	-3000	0.17	9	12	22	27	32	21	17	14
	Flow	-1500	0.04	9	11	21	27	32	22	18	15
		0		8	11	21	26	34	24	20	16
	Forward	+1500	0.04	7	11	20	25	32	24	20	16
	Flow	+3000	0.17	7	10	19	24	30	22	20	14

Forward Flow - characteristic of supply or discharge fan systems.

Reverse Flow - typical of return or intake fan systems.

Pressure Drop Calculation for Specific Velocity

Actual Velocity (fpm) = CFM x 144 , [3.14 x r² (in.)] r = radius

$$\text{Pressure Drop} = \left(\frac{\text{Actual Velocity}}{3000} \right)^2 \times \text{Catalog Pressure Drop @ 3000 fpm}$$

Standard Construction

10" - 24" diameter - 22 ga. galv.
26" - 60" diameter - 18 ga. galv.
24 gauge perforated baffles
Acoustic quality Fiberglass media

Optional Features

Mylar or polyethylene liners
Fiberglass cloth liners
Stainless steel or aluminum construction

Computer program available which provides attenuator performance at actual job conditions.



Tubular Attenuators

Self-noise Power Levels

Self-Noise Power Levels, dB re 10 ⁻¹² Watts Octave Band/Center Frequency (Hz)									
Model	Velocity fpm	1 63	2 125	3 250	4 500	5 1K	6 2K	7 4K	8 8K
RA	2000	59	57	51	47	47	45	42	33
	4000	69	68	70	71	64	66	61	57
RB	2000	62	59	51	47	47	44	39	36
	4000	68	67	59	55	57	55	49	52
DRA	2000	57	55	49	44	42	41	39	34
	4000	72	69	67	69	57	61	64	60
DRB	2000	55	53	46	43	41	40	37	32
	4000	69	65	64	65	52	57	59	56
DRC	2000	52	49	44	41	40	38	35	30
	4000	65	62	62	63	49	51	53	51
LRA	2000	57	55	49	44	42	41	39	34
	4000	72	69	67	69	57	61	64	60
LRB	2000	55	53	46	43	41	40	37	32
	4000	69	65	64	65	52	57	59	56
LRC	2000	52	49	44	41	40	38	35	30
	4000	65	62	62	63	49	51	53	51
RPS	2000	56	52	51	52	55	60	59	49
	4000	59	61	60	58	60	64	68	66
RPL	2000	45	44	40	39	41	36	26	20
	4000	57	57	55	54	55	58	57	48
REPL	2000	56	52	49	43	50	52	49	35
	4000	68	67	63	60	62	65	68	64

Area Correction Factors - Listed self-noise power levels are for silencers with a face area of 3.1 square feet. For silencers with different face areas, the following values must be added to those in the table. Area correction values do not apply to models RPS, RPL, or REPL.

Face area (sq. ft.)	0.75	1.5	2.5	3.1	4	6	8	15
PWL Correction Factors, dB	-6	-3	-1	0	1	3	4	7